LFH22-LAI200

21.5’’ Indoor Public View Monitor

Features :

- Built-in 2MP IPC provides clear and fine image of view
- Three mode:
  - public view: normaly advertisement and display IPC image when motion detection
  - surveillance view: display IPC image all the time
  - promtion view: display advertisement all the time
- Support built-in SD card for IPC storage
- Industrial design, support video, picture, text, audio and other multimedia information released, made for advertising industry
- Support remote timing switch function, can be customized holidays, spring, winter and other different dates, different time of the timer switch function
- Support remote screen capture function, look over the current play state of the terminal

Technical Specification

Model	
Model	LFH22-LAI200
System	
Diagonal	21.5"
Resolution	1920×1080 (FHD)
Backlight	LED
Brightness/Luminance (Standard)	250 cd/㎡
Contrast	3000:1
Angle of view	178°/178°(vertical/horizontal)
Response time	18ms
Basic Parameters	
Operating System	Android 4.4
CPU	Quad-core, 1.5G Hz
DDR	1G
NAND	8G
Communication Connection	WIFI/LAN
Decoding Ability	4CH@1080P
Ports	1 RJ45, 2 USB2.0, 1 RS232, 1 SD, 1TF
Speaker	8Ω, 2W x 2

Dimension	508x337x38 mm
Package Size	600×471×130 mm
Net Weight	5.9kg
Body Material	Metal plate
Protection	IP50
Installation Mode	Wall-mounted
Display Mode	Horizontal, Vertical
Power	DC12V
Standard Consumption	17.6W
Standard Consumption	0.3W
Work Environment	Temperature:-10℃~+55℃
	Humidity: 10%~90%
IP Rating	IP50
IPC Parameters	
Image Sensor	1/2.7“ CMOS
Effective Pixels	1920(H)×1080(V)
Minimum Illumination	3.6mm Manual 1/30s 1/25s(30 IRE) 0.15Lux/F2.0 (Color), 0.039Lux/F2.0(BW) Manual 1/3s 1/4s(100 IRE) 0.0158Lux/F2.0(Color), 0.000131Lux/F2.0(BW)